



Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 75kVA

By Acme Electric
Catalog # [TP530213S](#)



*Representative Image

Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 75kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection
- Optional weather shield - WSA3

General

ANFC Taps	2
BNFC Taps	4
Catalog Number	TP530213S
Construction	Ventilated
Electrostatic Shield	Shielded
Max Temperature Rise	150 Degrees Celsius
Mounting Type	Floor
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	220°C
UPC	047503087954
Winding Material	AL
kVA	75

Dimensions

Dimensions	26.88 in x 31.9 in x 35.47 in
Height	35.47 in
Length	26.88 in

Weight	430 lb
Width	31.9 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 X 480 V

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 2
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - TP530213S](#)
[SDS - HCC SDS](#)
[Specifications - TP530213S](#)
[Terms and Conditions - HCC Terms & Conditions](#)