



Die Cast 90° Squeeze Connectors for Flex

Innovative electrical fittings with premium quality and service offering more than 1,600 SKUs and numerous labor savings products

Features

- For use with armored cable, flexible metal conduit, interlocked metal clad cables, and HCF cables
- Male hub threads-NPSM
- Zinc die cast to prevent corrosion

Standard Materials

- Zinc Die Cast

Standard Finish

- Vibratory Finish

Applicable Third Party Standards

- CULUS 514B, File Number: E238299 | E207875
- NEMA FB-1



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Dim C (in)	Box	Case	Weight Per C (lb)	Insulated
MSCD3890-ICKON	3/8	1.26	1.34	1.89	25	250	8	Yes
MSCD3890KON	3/8	1.22	1.34	1.89	25	250	8	No
MSCD5090KON	1/2	1.50	1.65	2.07	15	150	12	No
MSCD5090-ICKON	1/2	1.54	1.65	2.07	15	150	12	Yes
MSCD7590KON	3/4	1.58	1.89	2.38	12	120	16	No
MSCD7590-ICKON	3/4	1.61	1.89	2.38	12	120	16	Yes
MSCD10090-ICKON	1	2.26	2.38	2.99	5	50	30	Yes
MSCD10090KON	1	2.22	2.38	2.99	5	50	30	No
MSCD12590-ICKON	1 1/4	2.82	2.68	4.02	4	40	44	Yes
MSCD12590KON	1 1/4	2.76	2.68	4.02	4	40	44	No
MSCD15090-ICKON	1 1/2	4.08	3.70	6.46	2	12	97	Yes
MSCD15090KON	1 1/2	4.02	3.70	6.46	2	12	97	No
MSCD20090KON	2	4.02	3.70	6.69	2	12	100	No
MSCD20090-ICKON	2	4.08	3.70	6.69	2	12	100	Yes
MSCD25090KON	2 1/2	6.77	5.18	3.92	1	10	209	No
MSCD25090-ICKON	2 1/2	6.77	5.18	3.92	1	10	209	Yes
MSCD30090-ICKON	3	7.78	5.87	4.72	1	4	286	Yes
MSCD30090KON	3	7.78	5.87	4.72	1	4	286	No
MSCD40090-ICKON	4	10.32	8.13	6.14	3		534	Yes
MSCD40090KON	4	10.32	8.13	6.14	3		534	No