



Die Cast Squeeze Connectors for Flex

Innovative electrical fittings with premium quality and service offering more than 1,600 SKUs and numerous labor savings products

Features

- For use with armored cable, flexible metal conduit, interlocked metal clad cables, and HCF cables
- Male hub threads-NPSM
- Zinc die cast to prevent corrosion

Standard Materials

- Zinc Die Cast

Standard Finish

- Vibratory Finish

Applicable Third Party Standards

- CULUS 514B, File Number: E207875



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Box	Case	Weight Per C (lb)	Insulated
MSCD50-ICKON	1/2	1.42	0.61	30	300	7	Yes
MSCD50KON	1/2	1.38	0.59	30	300	7	No
MSCD75KON	3/4	1.54	0.77	18	180	12	No
MSCD75-ICKON	3/4	1.57	0.79	18	180	12	Yes
MSCD100-ICKON	1	1.77	0.98	12	120	16	Yes
MSCD100KON	1	1.73	0.96	12	120	16	No
MSCD125KON	1 1/4	1.79	1.19	8	80	22	No
MSCD125-ICKON	1 1/4	1.85	1.19	8	80	22	Yes
MSCD150KON	1 1/2	1.89	1.42	6	60	30	No
MSCD150-ICKON	1 1/2	1.95	1.44	6	60	30	Yes
MSCD200-ICKON	2	2.09	1.93	4	40	35	Yes
MSCD200KON	2	2.03	1.92	4	40	35	No
MSCD250-ICKON	2 1/2	2.95	3.08	3	18	83	Yes
MSCD250KON	2 1/2	2.87	3.08	3	18	83	No
MSCD300-ICKON	3	3.33	3.58	2	12	147	Yes
MSCD300KON	3	3.25	3.58	2	12	115	No
MSCD400-ICKON	4	4.09	4.58	1	6	185	Yes
MSCD400KON	4	4.02	4.58	1	6	185	Yes