INCANDESCENT ROPE LIGHT

- Cost effective lighting for a variety of applications
- Flexible, cost effective linear lighting for a variety of applications
- Bright incandescent bulbs inside a colored PVC housing with nine different color options
- Bulk reels can be field cut every 18" for maximum project flexibility
- Each reel includes five connector kits and 50 mounting clips



INCANDESCENT



PART NUMBER	COLOR
1/2" Rope light - 150 ff	t - 5.5W per ft
RL-AM-150	AMBER
RL-BL-150	BLUE
RL-CL-150	CLEAR
RL-FR-150	FROSTED
RL-GR-150	GREEN
RL-PI-150	PINK
RL-PU-150	PURPLE
RL-RE-150	RED
RL-YE-150	YELLOW
3/8" Rope light - 150 ft - 5.5W per ft	
MRL-AM-150	AMBER
MRL-BL-150	BLUE
MRL-CL-150	CLEAR





POWER ACCESSORIES

PART NUMBER [DESCRIPTION
---------------	-------------

1/2" Rope Light Accessories

RL-LED-CONKIT-1.6AMP
RL-PWR
RL-INVSPL
RL-ST-3
RL-TRACK-4
Power connector kit with 120V AC power cord, power connector, end cap
Non-UL power connector
Invisible splice connecting sections of rope light; use with RL-ST-3
Clear shrink tube for use with invisible splice connections; 3" in length, sold in bags of 10
4ft long clear mounting track for straight line installations, with UV stabilizer for outdoor use

Clear "U" shaped mounting clip to securely hold rope light in place. Includes one mounting screw

3/8" Rope Light Accessories

RL-CLIP/SCREW

MRL-LED-CONKIT-1.6AMP Power connector kit with 120V AC power cord, power connector, end cap

MRL-LED-PWR Non-UL power connector

MRL-LED-INVSPL Invisible splice connector for connecting sections of rope light; use with MRL-ST-3

MRL-ST-3 Clear shrink tube for use with invisible splice connections; 3" in length, sold in bags of 10

MRL-TRACK-4 4ft long clear mounting track for straight line installations, with UV stabilizer for outdoor use

MRL-CLIP/SCREW Clear "U" shaped mounting clip to securely hold rope light in place. Includes one mounting screw



Power Connector Kit (RL-LED-CONKIT-1.6AMP) (MRL-LED-CONKIT-1.6AMP)



Power Connector (RL-PWR) (MRL-LED-PWR)



Splice Connector (RL-INVSPL) (MRL-LED-INVSPL)



Shrink Tube (RL-ST-3) (MRL-ST-3)



Mounting Track (RL-TRACK-4) (MRL-TRACK-4)



Mounting Clip (RL-CLIP/SCREW) (MRL-CLIP/SCREW)

TECHNICAL SPECIFICATIONS

Voltage 120V, 60Hz AC operation (1.6A inverter on power cord converts AC to DC)

Construction Heat resistant clear PVC housing with LEDs every 1", vertical mount

Cuttability AM, RE, YE = 60", BL, GR, WH and WW = 36" (no longer UL Listed if cut)

Wattage LED 0.8 watt per ft

Power cord 5 ft length with two blade polarized plug, white

Maximum run 150 ft length

Rated life 60,000 hours average rated life