



Overview

Model Name	APC Back-UPS 350
Includes	CD with software , Cord management straps , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Aruba , Bahamas , Barbados , Belize , Bermuda , Canada , Cayman Islands , Colombia , Costa Rica , Cuba , Dominican Republic , Ecuador , El Salvador , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Nicaragua , Panama , Puerto Rico , Trinidad And Tobago , Turks And Caicos Islands , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES)

Output

Output Power Capacity	210 Watts / 350 VA
Max Configurable Power (Watts)	210 Watts / 350 VA
Nominal Output Voltage	120V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Output Frequency (sync to mains)	Standby
Waveform Type	Stepped approximation to a sinewave
Output Connections	(3) NEMA 5-15R (Battery Backup) , (3) NEMA 5-15R (Surge Protection)

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P
Cord Length	1.83 meters
Input voltage range for main operations	98 - 140 V
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 hour(s)

Replacement Battery	RBC2
RBC Quantity	1

Communications & Management

Interface Port(s)	Optional Simple Signalling RS232 cable , USB
Available SmartSlot®; Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	1020 joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector)

Physical

Maximum Height	165.0 mm
Maximum Width	91.0 mm
Maximum Depth	284.0 mm
Rack Height	0 U
Net Weight	5.68 kg
Shipping Weight	6.36 kg
Shipping Height	263.0 mm
Shipping Width	175.0 mm
Shipping Depth	357.0 mm
Master Carton Units	2.0
Master Carton Weight	29.0 lbs
Color	Beige
SCC Codes	1073130401629 5
Units per Pallet	36.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB
Online Thermal Dissipation	20.000 BTU/hr

Conformance

Approvals	California (CEC) Battery Charger , ENERGY STAR (USA) , FCC Part 68 , TUV
Standard warranty	3 years repair or replace
Equipment protection policy	Lifetime : \$100000