

Product data sheet

Specifications



APC SERVICE BYPASS PDU, 120V 15AMP W/ (8) NEMA 5-15R

SBP1500RM

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Product or Component Type	Bypass kit
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	1
Provided Equipment	User Manual Rack Mounting brackets
Range of Product	Maintenance Bypass Panels

Physical

Color	Black
Height	3.50 in (8.9 cm)
Width	17.01 in (43.2 cm)
Depth	2.99 in (7.6 cm)
Product Weight	6.50 lb(US) (2.95 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Acceptable Input Voltage	100...125 V
Max line current	15 A
Input current limits	15 A
Load Capacity	1500 VA
Power factor	0...1

Output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum Total Current Draw per Phase	15 A
Number of power socket outlets	8 NEMA 5-15R
Number of power socket outlets	8
Protection Type	Circuit breaker
Cord Length	4 ft (1.2 m)
Efficiency	99 %

Conformance

Product Certifications	TÜV
------------------------	-----

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...15000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304266730
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.94 in (15.1 cm)
Package 1 Width	11.61 in (29.5 cm)
Package 1 Length	18.23 in (46.3 cm)
Package 1 Weight	8.4 lb(US) (3.8 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Take-back	No

Image of product / Alternate images

Alternative

