



Compression Connectors T&B Catalog Number:


AL 750 N 78378669406

Status: Active

Description:

UPC Number:

Aluminum Two-Hole NEMA Lugs - straight lug, concentric 750 and 700, ACSR 636 (26/7), installing dies 140H,301,342,1 1/2



Features	
	General purpose lugs for Aluminum and Copper terminations.
	Dual-rated. Use with Aluminum and Copper conductors.
	Made from Aluminum which provides high strength and high conductivity.
	Prefilled with Oxide Inhibitor to prevent oxidation and keeps out moisture.
	All lugs marked with conductor sizes and die references for easy identification.
General	
Style	Aluminum Lugs
Material	Aluminum
Dimension Information	
B (inches)	3 5/16
L (inches)	8 1/4
P (inches)	3 3/4
W (inches)	1 3/4
Conductor Size (ACSR)	636 (26/7)
Concentric	750, 700
Tooling	
Installing Dies	140H,301,342,1 1/2
Notes	
	For tin plating option, add 'TN' suffix to the catalog number. All tin-plated lugs are UL Listed through 1000 kcmil.
	For straight lugs with tapered ends used in high-voltage applications, please consult your Thomas & Betts representative.
	Dimension (W) is trimmed to 1 3/4" maximum to fit side by side on NEMA spades.
Certifications	
Standards Compliant	Meets or exceeds ANSI C119.4 specifications.

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com