

Actual

Family

Catalog Number: OAPA-1000
Product ID: 7TAA007480R0024
UPC Number: 07511413388
Status: Active

Aluminum Solid Pin Terminals Offset Pin Style with Insulating PVC Boot, Wire Size 1000 kcmil, Overall Length 4.03 Inches (102.36mm), Tin Plated, Die Code 140, NA

- Tooth design to provide greater holding force. One piece connector design for increased reliability.
- UL Listed with T&B and competitor application tooling.
- Pin designed to have greater cross-sectional area than conductor. EPDM rubber or PVC boot provided to eliminate the need for any taping.
- Termination of aluminum or copper conductors to mechanical lugs.

UNSPSC Specifications

UNSPSC	39121405 Cable or wire lug
IGCC	4532 Cable or wire lug
Brand Name	Blackburn
Type	Pin Adapters
Application	Termination of aluminum or copper conductors to mechanical lugs.
Cable Size	1000 kcmil
Voltage Rating	600V
Material	Aluminum

Packaging

Outer Quantity	3
Outer Dimensions (inches)	7.3x7x4.6
Weight Uom	0.53 lbs. Each

Documents / Support Tools

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com