



# Locking Devices, Bryant Power Interrupting, Industrial, Receptacle, 30A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

By Bryant  
Catalog # 20403



Locking Devices, Bryant Power Interrupting, Industrial, Single Receptacle, 30A 600V AC/ 20A 250V DC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black, For F.S. and F.D. boxes

## Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Thermoset molded housing provides maximum heat resistance

## Application

- Extra Heavy Duty Industrial Specification Grade

## General

Catalog Number	20403
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	20A/30A Single Receptacle
Material	Composite
Material - Mounting Hardware	Screw Mounting
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Bryant
Style	Grounding
Type	Receptacle
UPC	781786618473

## Dimensions

Dimensions	3.28 in x 1.94 in x 1.75 in
Display Size	Standard Sized Product
Height	1.75 in
Length	3.28 in
Width	1.94 in

## Electrical Ratings

Amperage Rating	20A/30 A
Connectivity	Terminal Screws
Current Amperage Description	20 Amp /30 Amp
Current Rating	20A/30 A
Phase	Single Phase
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

## Conductor Related

Number Of Wires	4-Wire
Wire Size	#14 AWG to #10 AWG

## Logistics

Carton Quantity	20
-----------------	----

## Product Assets

[Catalog Page - BRY H-25 Catalog Page](#)  
[Catalogs - Bryant Full Line Catalog](#)  
[Specifications - 20403](#)