

# **GAR6429, Mechanical Grounding** Connector, Cable to Rod or Pipe

By Burndy Catalog # GAR6429

Mechanical Grounding Connector, Cable to Rod or Pipe, 2/0 AWG (Sol) -250 kcmil, 3/8" Pipe, 5/8"-3/4" Rod, #5-#6 Rebar, Bright Dipped.



## **Application**

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

#### General

Catalog Number GAR6429 **EU RoHS Indicator** Installation Torque 240 lb-in Recommended in-lb

Material Copper Alloy

Material - Hardware DURIUM™ Silicon Bronze

Plated

**Bright Dipped** Plating Type

Sub Brand MECHANICAL CONNECTOR

GAR Type U Bolt Type 269

UPC 781810238400 UPC 12 Digit 7818102384000

#### **Dimensions**

Dimension - B Length inch 1.75 in Dimension - Height fraction 2-7/8 in Dimension - Height inch 2.88 in Dimension - L Length Overall 46 mm 1.81 in Dimension - Length Overall inch Dimension - Outside Diameter 0.68 in inch Dimension - Width fraction 2-1/8 in Dimension - Width inch 2.06 in Dimension - Width mm 52 mm

#### **Conductor Related**

Conductor - Copper Solid Size 2/0 AWG;3/0 AWG;4/0 AWG Conductor - Copper Solid Size 2/0 AWG - 250 kcmil

Range

1/0;2/0 AWG;3/0 AWG;4/0 Conductor - Copper Str Size

AWG;250 kcmil

Conductor - Copper Str Size 1/0 AWG - 250 kcmil

Range

Conductor - Copper Tube Std 3/8 IPS IPS

Conductor - Copper Tube Std 3/8 IPS IPS

Size Range

Conductor - Pipe or Round 3/8 in

Tube Size

Conductor - Rebar Size 5;6

Conductor - Rebar Size Range 5 -6

Conductor - Rod Size

Conductor - Rod Size Range

Conductor Type

0.625in - 0.75in

5/8 in-3/4 in

• CU C Solid-Size

• CU C Str-Size

• CU Tube Std-Size

Rod-Size

Yes

#### **Certifications And Compliance**

| Certification - CSA Approved               | No    |
|--|-------|
| Certification - ETL                        | No    |
| Certification - UL Listed Direct<br>Burial | Yes   |
| Certification - UL Recognized              | No    |
| Certification - cULus                      | No    |
| Industry Standard(s)                       | UL467 |
| Standards - Industry<br>Standards Met      | UL467 |
| Standards - RoHS Compliance<br>Status      | EX    |
|  |       |

# **UL** Listed Logistics

Minimum Pack Quantity

## **Product Assets**

3D Models - GAR6429\_MODEL-STEP 3D Models - GAR6429 MODEL-IGES 3D Models - GAR6429\_MODEI-PDF

Catalogs - Full Line BURNDY Catalog

Catalogs - Section F2 - Mechanical Grounding

Customer Notices - Prop 65 Notice Product Cross Section Image(s) - BUR\_GAR\_Lineart Sales Drawings - SD..015789-01



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. BRDY-GAR6429-SPEC-EN | REV 6/2024