



## K2A26U, AL Universal Terminal, 2 Conductor, 1-Hole, #14-2/0 AWG, 1/4" Stud, 2 Screws, Al/Cu Rated

By Burndy  
Catalog # [K2A26U](#)

Aluminum Universal Terminal, 2 Conductor, 1 Hole, 14-2/0 AWG (Str), 1/4" Stud, 2 Screws, Al/Cu Rated, Tin Plated.



### Features

- Dual rated panelboard lugs constructed from high strength extruded aluminum alloy , electro tin-plated to provide low contact resistance

### Application

For Aluminum And Copper Conductors

### General

|                                       |                           |
|---------------------------------------|---------------------------|
| Catalog Number                        | K2A26U                    |
| Connector Type                        | Parallel Set-Screw        |
| EU RoHS Indicator                     | No                        |
| Hardware Type                         | 3/8 UNC Slotted Set Screw |
| Installation Torque Recommended in-lb | 120 LBS/in                |
| Material                              | Aluminum                  |
| Material - Hardware                   | Aluminum                  |
| Physical Attribute - Number of Holes  | 1                         |
| Physical Attribute - Screw Type       | Slot                      |
| Plated                                | N                         |
| Plating Type                          | Tin plated                |
| Sub Brand                             | UNIVERSAL TERM            |
| Temperature Rating                    | 194                       |
| Type                                  | Bolted Lugs & Terminals   |
| UPC                                   | 781810600054              |
| UPC 12 Digit                          | 7818106000544             |

### Dimensions

|                                 |         |
|---------------------------------|---------|
| Dimension - Bolt Hole Size inch | 0.25 in |
| Dimension - Bolt Size fraction  | 1/4     |
| Dimension - D inch              | 0.81 in |
| Dimension - Height fraction     | 4/5 in  |
| Dimension - Height inch         | 0.80 in |
| Dimension - Hole Size inch      | 0.27 in |
| Dimension - Hole Size mm        | 7 mm    |
| Dimension - L Length Overall mm | 37 mm   |
| Dimension - Length Overall inch | 1.47 in |
| Dimension - N inch              | 0.44 in |
| Dimension - Pad Width inch      | 1.27 in |
| Dimension - Screw Size inch     | 3/8     |
| Dimension - Stud Size inch      | 1/4 in  |

### Conductor Related

|                                   |                                                                                         |
|-----------------------------------|-----------------------------------------------------------------------------------------|
| Conductor - AL Str Size           | 8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG                                     |
| Conductor - AL Str Size Range     | 14 Str-2/0 AWG                                                                          |
| Conductor - Copper Str Size       | 14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG |
| Conductor - Copper Str Size Range | 14 Str-2/0 AWG                                                                          |
| Conductor Size                    | 14-2/0 AWG                                                                              |
| Conductor Type                    | <ul style="list-style-type: none"><li>AL C Str-Size</li><li>CU C Str-Size</li></ul>     |
| Number of Conductors              | 2                                                                                       |

### Certifications And Compliance

|                                         |              |
|-----------------------------------------|--------------|
| Certification - CSA Approved            | Yes          |
| Certification - UL Listed Direct Burial | No           |
| Industry Standard(s)                    | UL 486A-486B |
| Standards - Industry Standards Met      | UL 486A-486B |
| Standards - RoHS Compliance Status      | EX           |
| UL Listed                               | Yes          |

### Logistics

|                       |     |
|-----------------------|-----|
| Carton Quantity       | 432 |
| Minimum Pack Quantity | 1   |

### Product Assets

[3D Models - K2A26U\\_MODEL-PDF](#)  
[3D Models - K2A26U\\_MODEL-STEP](#)  
[3D Models - K2A26U\\_MODEL-IGES](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Catalogs - Section A - Mechanical](#)  
[Customer Notices - Prop 65 Notice](#)  
[Product Cross Section Image\(s\) - BUR\\_K2AU\\_Lineart](#)  
[Sales Drawings - se210997](#)

|                            |          |
|----------------------------|----------|
| Dimension - Stud Size inch | 1/4 in   |
| Dimension - Width fraction | 1-1/4 in |
| Dimension - Width inch     | 1.27 in  |
| Dimension - Width mm       | 32 mm    |

**Electrical Ratings**

|                          |     |
|--------------------------|-----|
| Rating - Minimum Voltage | 600 |
|--------------------------|-----|



A proud member of the Hubbell Family.