

YGHA252N Compression Grounding Lug, 1/0 AWG Cu, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy Catalog # YGHA252N

Copper Compression Lug, Heavy Duty, 2 Hole w/ Inspection Probe Hole, 1/0 AWG, 1/2" Stud, 1.75" Stud Hole Spacing, Short Barrel



Application

For Direct Burial In Earth Or Concrete, Grounding Applications

General

Connector Type Terminal
Die Index 14
EU RoHS Indicator Yes
Material Copper

Physical Attribute - Number of 1

Crimps Required

Plated N

Plating Type Unplated
Sub Brand HYLUG
Trade Name HYLUG™
Type Terminals
UPC 781810220610
UPC 12 Digit 7818102206100

Dimensions

Dimension - B Length fraction 39/47 in
Dimension - B Length inch 0.83 in
Dimension - D inch 3.00 in
Dimension - Hole Size inch 0.56 in
Dimension - Hole Size mm 14 mm
Dimension - L Length Overall 117 mm
mm

Dimension - Length Overall

inch

Dimension - N inch 0.63 in Dimension - Outside Diameter 0.63 in

inch

Dimension - Pad Width inch

Dimension - Stud Size fraction

Dimension - Stud Size inch

Dimension - Z (inch)

Physical Attribute - Tonque

O.91 in

0.91 in

0.91 in

0.91 in

0.92 in

Straight

Angle

Conductor Related

Conductor - Copper Str Size 1/0 AWG
Conductor - Copper Str Size 1/0 AWG

Range

Conductor Type • CU C Str-Size

• CU C Solid-Size

Certifications And Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Listed Direct Yes
Burial
Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) • UL467

• UL 486A-486B

• IEEE 837

Standards - Industry UL467;UL 486A-486B;IEEE Standards Met 837

Standards - RoHS Compliance CN

Status

UL Listed Yes

Logistics

Carton Quantity 10
Minimum Pack Quantity 1
Pallet Quantity 9600

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..082472-01



4.60 in