# Eaton 100FE

## Catalog Number: 100FE

Eaton Bussmann series high speed British standard fuse, Single barrel, 100A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

## General specifications



Eaton Bussmann series high speed

british standard fuse

EAN

5027590427647

**Product Height** 

39 mm

**Product Weight** 

41.2 g

Compliances

CE Marked RoHS Compliant Catalog Number

100FE

UPC

051712830270

Product Length/Depth

82 mm

Product Width

91 mm

Warranty

Not Applicable



## Electrical data

**Amperage Rating** 

100 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

470

Clearing (I2T)

1800 at 415 V, 2800 at 660 V

Watt losses

23 W

## **Product specifications**

#### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

#### Fuse indicator

None

## Compatble Trip indicator/Microswitch

#### Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

#### Resources

#### **Brochures**

 $eaton-bus smann-series-bs 88-high-speed-fuses-product-aid-\\pal 35003 en-us.pdf$ 

## Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

## Certification reports

DA-DC-00004685

DA-DC-00004682

#### Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia