

Datasheet

IP-SDS - PoE Single Door Station

Product Description

CDVI's intercom system provides video entry solutions for residential and commercial properties alike. With both IP and a free smartphone app, take advantage of a flexible, affordable and reliable security system.

The IP-SDS is a single-button station ideal for a single-home or small business. Up to 32 monitors can be connected this device. Pushing the button will call all monitors inside the building.

The IP system facilitates connection through PoE, making the intercom system seamless and easy to use.



Key Features

- 1-button station
- PoE
- Audible annunciation
- Surface mount
- 170° fisheye camera

 Certification

 DEEE


RoHS Certification

 IP54

 14°F to 131°F
(-10°C to 55°C)

Product Specifications

Material:	Stainless steel panel
Mounting:	Surface mount
Technology:	IP
Camera:	Type 1/3.7" Ultra Sense, ISP with 77dB WDR, 170° fish-eye lens
Unlocking time:	1 to 99s
Relay:	1
Cable type:	Cat5e or Cat6
Weight:	0.6 lb, 0.4 kg



Electrical Specifications

Power input:	24 V DC
Consumption:	Standby: 15 mA Working: 105 mA3
Lock power supply:	12 V DC, 280 mA (Internal power - fail secure only)

Accessories



IP-MONSQ

PoE Touch Screen Monitor – Square



IP-POE4/8

4/8-port PoE+ switch (32 W)



Download the app

today!



Datasheet

IP-MON, IP-MONSQ - PoE Touch Screen Monitor

Product Description

The IP-MON & IP-MONSQ is a white, touch-screen, TFT monitor. The IP system facilitates connection through PoE, making the intercom system seamless and easy to use. Free to download on iOS and Android, use the VDP Connect app to easily communicate with visitors at the door station and control door locks remotely. The IP-MON has a rectangular shape and the IP-MONSQ has a square shape.

IP-MON



IP-MONSQ



Key Features

- 7" touch screen, fingerprint resistant
- SIP Server
- Call recording and built-in memory
- Surface mount
- Mobile application available
- Also available in black : IP-MONB

 Certification

 DEEE



RoHS Certification

 14°F to 131°F
(-10°C to 55°C)

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 22 August 2023. CDVI_IP-MON_IP-MONSQ_DS_01_EN_LETTER_C

Product Specifications

Material:	
Mounting:	Surface, vertical or horizontal
Technology:	IP video entry
Screen size:	7 inches
Resolution:	1024 x 600 pixels
Memory:	Supports SD cards up to 512GB (not supplied)
Cable type:	Cat-5e or Cat-6
Weight:	1 lb, 0.45 kg



Electrical Specifications

Power input:	PoE (IEEE 802.3af Class 0)
Consumption:	PoE: Standby: 40.9 mA / Working: 69.8 mA 28 V DC: Standby: 92.9 mA / Working: 152.6 mA

Accessories



IP-SDS

PoE Single Door Station



IP-MDS

PoE Multi-Tenant Station (Surface Mount)



Download the app!



Datasheet

IP-POE4/8 - 4/8 Port PoE+ switch (32 W)

Product Description

CDVI's intercom system provides video entry solutions for residential and commercial properties alike. With both IP and a free smartphone app, take advantage of a flexible, affordable and reliable security system.

The IP-POE4 is a 6-port 10/100Mbps switch with 4 PoE ports (#1-4).

The IP-POE8 is a switch that contains 10 RJ45 ports, 8 of which support PoE functions.



IP-POE4



IP-POE8

Key Features

- PoE switch with 4 or 8 PoE ports
- Supports up to 32W for each PoE port
- Panel lights to monitor working state
- 2 ethernet ports (in/out)
- 10/100 Mbps



Certification



DEEE





Certification



32°F to 122°F
(0°C to 50°C)

Product Specifications

Mounting:	Desktop, wall-mount
Technology:	Power Over Ethernet
Standards:	IEEE 802.3af, IEEE 802.3x
Interfaces:	4-way: 10/100 Mbps RJ-45 8-way: 100Base-TX RJ-45 PoE+ - 30W, 1 x Gigabit LAN SFP, 1 x 1000Base-T RJ-45
Total PoE budget:	4-way: 41W 8-way: 124W
Packet forwarding rate:	4-way: 0.744 Mpps 8-way: 4.166 Mpps
Switching capacity:	4-way: 1 Gbps 8-way: 5.6 Gbps
Weight:	PoE-4: 1 lb, 0.45 kg PoE-8: 1.3 lb, 0.5 kg



Electrical Specifications

Power input:	External power adaptor
Consumption:	47W (4-way)

Accessories



IP-SDS

PoE Single Door Station



IP-MDS

PoE Multi-Tenant Station (Surface Mount)



IP-MON

PoE Touch Screen Monitor