

Fix-It-Foot

Additional vibration isolation and stability

FEATURES

- Idea for rooftop support of equipment & systems
- Weather resistant
- Recycled crumb rubber pad
- Recessed underside permits solid stance
- Aluminum track permits the use of standard strut hardware (not included)

Max load capacity: 87771 (RMB10) - 356 lbs.
 87773 (RMB16) - 572 lbs. 87775 (RMB24) - 1045 lbs.
 87776 (RMB40) - 1420 lbs.



Fix-It-Foot Low

Low profile rubber riser

FEATURES

- Idea for rooftop support of equipment & systems
- Weather resistant
- Recycled crumb rubber pad
- Recessed underside permits stability
- Aluminum track permits the use of standard strut hardware (not included)

Max load capacity:
 87772 (RMB10L) - 356 lbs. 87774 (RMB16L) - 572 lbs.



Multi Foot

Frame support ideal for smaller systems

FEATURES

- Strong and Lightweight
- Weather resistant PVC - Rubber/PVC
- Linear track holds 1/2" hex head bolts
- Two 7/8" long bolts included

Max load capacity:
 87711 (RSP16) - 572 lbs. 87712 (RSP24) - 1045 lbs.



H-Frame

Accepts standard 1 5/8" strut, optimum support

FEATURES

- Idea rooftop support of equipment & systems
- Weather resistant
- Recycled crumb rubber pad
- Recessed underside permits stability
- Aluminum track permits the use of standard strut hardware (not included)

Max load capacity: 87713 (RSPD12) - 330 lbs.
 87714 (RSPD18) - 661 lbs. 87715 (RSPD24) - 992 lbs.

