

Eaton DCU1062URM

Catalog Number: DCU1062URM

Eaton heavy duty DC disconnect,For Ungrounded PV Systems,DC disconnect/ungrounded system,60A,NEMA 3R,Painted galvanized steel,Non-fusible,Ungrounded,#14-#2 AWG lug capacity, #14-1/0 AWG solid return,600 Vdc,1,DC Photovoltaic Applications

General specifications

Product Name	Catalog Number
Eaton heavy duty DC disconnect	DCU1062URM
UPC	Product Length/Depth
786685556956	9.89 in
Product Height	Product Width
16.27 in	8.87 in
Product Weight	Warranty
20 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Certifications	Catalog Notes
UL 98B NEC 690 per UL 1741	Not all configurations for ampere rating and number of circuits are available. All circuit configurations can be found in the product dimension tables.



Product specifications

Special features

For Ungrounded PV Systems

Maximum voltage

600 VDC

Switch type

Heavy duty

Ground

Ungrounded

Fuse configuration

Non-fusible

Enclosure

NEMA 3R

Amperage Rating

60 A

Enclosure material

Painted galvanized steel

Series

DC Photovoltaic Applications

Type

DC disconnect/ungrounded system

System voltage

600 VDC per pole

NEMA rating

NEMA 3R

Main lug wire size

#14-#2 AWG lug capacity, #14-1/0 AWG solid return

Number of circuits

1

Voltage rating

600 VDC

Protection

Non-fusible

Application

Solar

Resources

Brochures

[DC disconnects for grounded and ungrounded photovoltaic installations](#)

Multimedia

[Switching Devices Flex Center](#)

[Double Up on Safety](#)

Specifications and datasheets

[Eaton Specification Sheet - DCU1062URM](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)