

Specifications



Photo is representative

Eaton 1350E-6504

Eaton Enhanced 50 Series Photoelectric Sensor, Photoelectric, Right Angle, Sensor distance: 5 Ft., 3A max AC, SPDT Form C Relay, 3A at 240 Vac, 5 Pin Mini Connector, 12-240 Vdc 24-240 Vac input, Diffuse Reflective

General specifications

PRODUCT NAME	Eaton Enhanced 50 photoelectric sensor
CATALOG NUMBER	1350E-6504
UPC	782116111558
PRODUCT LENGTH/DEPTH	1.91 in
PRODUCT HEIGHT	4.16 in
PRODUCT WIDTH	1.81 in
PRODUCT WEIGHT	0.3375 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified
PRODUCT TYPE	Photoelectric sensor



Powering Business Worldwide

Product specifications

CONTACT RATING	3A at 240 Vac
ENCLOSURE MATERIAL	Fiberglass reinforced plastic
OPERATING MODE	Diffuse reflective
CONNECTION	5-pin mini connector
CONTACT CONFIGURATION	SPDT form C relay
SENSOR TYPE	Diffuse reflective
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	12-240 Vdc, 24-240 Vac
LED INDICATOR	Output status: green Marginal gain: red Power on: yellow
MAXIMUM AC CURRENT	3 A
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	IP67, IP69K

Resources

CATALOGS	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 1350E-6504

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

