

- 1 High impact-resistant housings for long-term durability
- 2 Plug blades firmly embedded in body
- 3 Angled plugs allow placement of cords in convenient locations
- 4 Heavy Duty Grade plugs feature solid brass plug blades and terminals in individual chambers for positive conductor insulation
- 5 Heavy Duty Grade plugs & connectors feature strain relief clamps to extend cord life
- 6 Spring Action plugs & connectors are designed for easy installation and some also provide an integrated cord clip for storage on appliances
- 7 Academy Series plugs feature insulation-piercing terminals that eliminate wire stripping



## Specific Plug & Connector Solutions for Today's Needs



### Extension Cords

Heavy-duty extension cord ends receive a lot of abuse in working situations. QuickGrip™ plugs & connectors install easily, speeding replacement, and are built to last.



Shown:  
AH5965

See  
pages:  
B-40  
B-41



### Cold Conditions

Most plastics become more brittle and the chance of breakage increases below freezing. Rubber plugs & connectors keep flexibility in lower temperatures for less breakage.



Shown:  
1709

See  
page:  
B-43



### Appliance Cord End Replacement

Household appliances often require cord end replacement. Spring Action plugs are available with cord clips and are quick and easy to install.



Shown:  
SA940

See  
page:  
B-44

## Heavy Duty Grade Rubber Plugs & Connectors

2-Pole, 3-Wire Grounding  
15A, 125V/AC



5-15P



5-15R

### FEATURES

- Solid brass plug blades are firmly embedded in body.
- Thermoplastic rubber plugs & connectors maintain flexibility in extremely low temperatures.
- Terminals in individual chambers to positively insulate conductors.
- Terminal screw clamps are designed to contain wire and prevent binding.
- Terminal screws backed out and ready for wiring.
- Combination Slot/Phillips head mounting and terminal screws for installation flexibility (Slot/Robertson screws in Canada where available).



1709

## Thermoplastic Rubber Plugs & Connectors

15A 125V/AC

Description	Cord Diameter	Color	Plug	Catalog No.	
				Plug	Connector
15A NEMA 5-15, Straight Body	0.25-0.60" (6.4-15.2mm)	Black	<input type="checkbox"/> 1709	<input checked="" type="checkbox"/>	<input type="checkbox"/> 222 <input checked="" type="checkbox"/>

1709: cULus Listed to UL498, file no. E15012; NOM certified


222: Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified

## Standard Grade Rubber Plugs & Connectors

2-Pole, 2-Wire Non-Grounding  
15A, 125V/AC



1-15P



1-15R

### FEATURES

- Plug blades are firmly embedded in body.
- Rubber plugs & connectors maintain flexibility in low temperatures.
- Angle plugs allow placement of cord in convenient location.
- Terminal screws backed out and ready for wiring.
- Combination Slot/Phillips head mounting and terminal screws for installation flexibility (Slot/Robertson screws in Canada where available).



183

## Rubber Plugs & Connectors

15A 125V/AC

Description	Cord Diameter	Color Suffix	Plug	Catalog No.	
				Plug	Connector
NEMA 1-15, Straight Body	0.33" (8.3mm)	BK, W	<input type="checkbox"/> 183__	<input checked="" type="checkbox"/>	<input type="checkbox"/> 86__ <input checked="" type="checkbox"/>
NEMA 1-15, Straight Body, Polarized	0.33" (8.3mm)	BK, W	<input type="checkbox"/> 183-6__	<input checked="" type="checkbox"/>	—
NEMA 1-15, Angled Body	0.33" (8.3mm)	BK	<input type="checkbox"/> 84__	<input checked="" type="checkbox"/>	—
NEMA 1-15, Angled Body, Polarized	0.33" (8.3mm)	BK, W	<input type="checkbox"/> 84-6__	<input checked="" type="checkbox"/>	—

Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified except 86



86

**Color Ordering Information:** For ordering devices, include Cat. No. followed by the color code if applicable: BK (Black), W (White)

**Dimensional Information:** B-62 – B-63

**Specification Information:** Please visit [www.cooperwiringdevices.com](http://www.cooperwiringdevices.com)

**NAFTA Compliant:** See page F-21