



Complex environment locking devices

Product description

2-pole, 3-wire grounding
20A, 250V/AC
NEMA L6-20



Plugs & connectors



Rating A	V/AC	NEMA	Description	Cord Diameter	Color	Plug catalog no.	Connector catalog no.		
20	250	L6-20	Watertight	0.36-0.84" (9.1-21.3mm)	Y	□ L620PW	□ L620CW	•	•
			Watertight	0.36-0.84" (9.1-21.3mm)	BK	□ L620PWBK	□ L620CWBK	•	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L620PY	□ L620CY	•	•
			Safety grip corrosion resistant	0.38-1.00" (9.7-25.4mm)	Y	□ CRL620P	—	•	•

* Not Fed Spec

Receptacles




Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
20	250	L6-20	Watertight	Y	□ L620RW*	•	•
			Watertight	BK	□ L620RWBK*	•	•
			Corrosion resistant	Y	□ CRL620R	•	•

*Not Fed Spec

Complex environment locking devices

Product description

2-pole, 3-wire grounding
20A, 277V/AC
NEMA L7-20



Plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	277	L7-20	Watertight	0.36-0.84" (9.1-21.3mm)	Y	□ L720PW	□ L720CW	•	
			Watertight	0.36-0.84" (9.1-21.3mm)	BK	□ L720PWBK	□ L720CWBK	•	
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L720PY	□ L720CY	•	

Receptacles



Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
20	277	L7-20	Watertight	Y	□ L720RW	•	•
			Watertight	BK	□ L720RWBK	•	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40
Corrosion resistant: D-41

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32