

Specifications



Photo is representative

Eaton P48G11S0512CU

5 KVA Mini Power Center 1PH 480-120/240
115C RISE 12 spaces

General specifications

PRODUCT NAME	Eaton Mini-Power center
CATALOG NUMBER	P48G11S0512CU
UPC	786680226267
PRODUCT LENGTH/DEPTH	8.9 in
PRODUCT HEIGHT	29.5 in
PRODUCT WIDTH	11.9 in
PRODUCT WEIGHT	1.1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NAFTA
CERTIFICATIONS	IEEE Certified CSA Certified UL Listed ANSI

Physical Attributes	
COIL MATERIAL	Copper
ENCLOSURE	NEMA 3R
FRAME	284
INSULATION	180 °C
MOUNTING	Wall Mount
TAP SIZE	2 at -5% FCBN
TYPE	Mini-power center
WIRING CONNECTION	M48G11D

Miscellaneous	
MODIFICATION 1	NEMA 3R
WEATHERSHIELD	Not required

Performance Ratings	
FREQUENCY RATING	60 Hz
KVA	5 kVA
KVA RATING	5 kVA
PHASE	Single-phase
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	120/240 V
SOUND LEVEL	NEMA ST-20
TEMPERATURE RISE	115 °C rise
VOLT AMPERE RATING	5 kVA

Resources	
CATALOGS	Commercial Distribution Transformers, Volume 2, Tab 2
MULTIMEDIA	Eaton's Transformer Flex Center
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - P48G11S0512CU

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

