




High Lumen T8 Linear

For spaces that demand uncompromising light

- High efficacy – 150 lm/W
- High lumen output - 18W (2700lm), 24W (3600lm)
- Flexible wiring configuration - single-ended + double ended
- CCT: 4000K, 5000K
- Available in Type-B (ballast-bypass) and Type A+B models
- Glass construction – reduces visual glare and provides optimal heat dissipation



Applications



Office & Indoor
Workspaces



Education



Grocery &
Retail



Warehouses



Factories

Order#	Name	Lumens	Watts	CCT	Voltage
	Type B				
15577	L18WT8-48-BSDG-840	2700 lm	18W	4000K	120-277V
15578	L18WT8-48-BSDG-850	2700 lm		5000K	
15579	L24WT8-48-BSDG-840	3600 lm	24W	4000K	
15580	L24WT8-48-BSDG-850	3600 lm		5000K	
	Type A+B				
15581	L18WT8-48-ABSDG-840	2700 lm	18W	4000K	120-277V Type A (Ballast Voltage) or Type B (Line Voltage)
15582	L18WT8-48-ABSDG-850	2700 lm		5000K	
15583	L24WT8-48-ABSDG-840	3600 lm	24W	4000K	
15584	L24WT8-48-ABSDG-850	3600 lm		5000K	