

LED FILAMENT DECORATIVE

DESCRIPTION

LED Filament Decorative Replacement Lamps are a cost-effective, energy-efficient alternative to incandescent filament lamps.

FEATURES

- LED lamp with the same vintage look and feel as traditional incandescent filament lamps
- 80% more efficient and 20x longer life than incandescent
- 2200K amber and 2700K clear available in various decorative shapes
- Compatible with a wide array of leading edge TRIAC dimmers
- Suitable for use in totally enclosed fixtures
- Dimmable down to 10% of full light output
- Not intended for use with emergency exits

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Chandeliers
- Accent/display lighting
- Sconces
- Lanterns
- Hospitality
- Residential
- Vanity mirrors



Top: A15; A19; A19 Silver Bowl; ST19
Middle: G16; G25; S14
Bottom: B11 E26; B11 E12; BA11 E12; T10; T6 E12; T6.5 E17

RoHS
Compliant

cUL US LISTED

PERFORMANCE	Power Consumption	2.5W	4W	4.5W	5W	7W
	Lumens	200/250	250/300/350/400	350/400/450/470/500	500	700/800
	Efficacy (LPW)	80/100	63/75/88/100	78/89/100/104/111	100	100/114
	CRI	80+				
	CCT	2200K, 2700K				
	Life (L70)	15,000 hours				
ELECTRICAL	Power Factor	≥0.9				
	THD	<20%				
	Input Voltage	120VAC				
CONSTRUCTION	Lens	Frosted				
	Base	G5				
LISTINGS	Certification(s)	cULus Listed				
	Material Usage	RoHS Compliant; no mercury or lead				
	Environment	Suitable for use in damp locations				

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	Volts	Shape	Base	MOL	MOD	Life/Hours
09858	LED2.5WB11E12/FIL/827-DIM-G7	200	2.5W	2700K	80+	120VAC	B11	E12	3.8/96.6	1.38/35	15,000
09869	LED2.5WT10/FIL/827-DIM-G7	250	2.5W	2700K	80+	120VAC	T10	E26	5.31/135	1.3/33	15,000
09866	LED2.5WT6.5E17/FIL/827-DIM-G7	200	2.5W	2700K	80+	120VAC	T6.5	E17	4.65/118	0.79/20	15,000
09865	LED2WT6E12/FIL/827-DIM-G7	120	2W	2700K	80+	120VAC	T6	E12	3.15/80	0.71/18	15,000
09856	LED4.5WA15/FIL/827-DIM-G7	450	4.5W	2700K	80+	120VAC	A15	E26	3.46/88	1.89/48	15,000
09871	LED4.5WA19/FIL/822-DIM-G7	350	4.5W	2200K	80+	120VAC	A19	E26	3.94/100	2.36/60	15,000
09857	LED4.5WA19/FIL/SB/827-DIM-G7	400	4.5W	2700K	80+	120VAC	A19	E26	3.94/100	2.36/60	15,000
09859	LED4.5WB11E12/FIL/827-DIM-G7	500	4.5W	2700K	80+	120VAC	B11	E12	3.8/96.6	1.38/35	15,000
09862	LED4.5WG16/FIL/827-DIM-G7	500	4.5W	2700K	80+	120VAC	G16	E26	3.15/80	2.17/55	15,000
09875	LED4.5WG25/FIL/827-DIM-G7	470	4.5W	2700K	80+	120VAC	G25	E26			15,000
09868	LED4.5WT6.5E17/FIL/827-DIM-G7	450	4.5W	2700K	80+	120VAC	T6.5	E17	4.65/118	0.79/20	15,000
09855	LED4WA15/FIL/827-DIM-G7	300	4W	2700K	80+	120VAC	A15	E26	3.46/88	1.89/48	15,000
09892	LED4WB11E12/FIL/827-DIM-G7	300	4W	2700K	80+	120VAC	B11	E12	3.8/96.6	1.38/35	15,000
09860	LED4WBA11E12/FIL/827-DIM-G7	400	4W	2700K	80+	120VAC	BA11	E12	4.84/123	1.38/35	15,000
09861	LED4WG16/FIL/827-DIM-G7	350	4W	2700K	80+	120VAC	G16	E26	3.15/80	2.17/55	15,000
09864	LED4WS14/FIL/827-DIM-G7	300	4W	2700K	80+	120VAC	S14	E26	3.19/81	1.77/45	15,000
09863	LED4WS14/FIL/822-DIM-G7	250	4W	2200K	80+	120VAC	S14	E26	3.19/81	1.77/45	15,000
09879	LED4WST19/FIL/822K-DIM-G7	400	4W	2200K	80+	120VAC	ST19	E26			15,000
09870	LED4WT10/FIL/827-DIM-G7	450	4W	2700K	80+	120VAC	T10	E26	5.31/135	1.3/33	15,000
09867	LED4WT6.5E17/FIL/827-DIM-G7	300	4W	2700K	80+	120VAC	T6.5	E17	4.65/118	0.79/20	15,000
09878	LED5WB11E26/FIL/827K-DIM-G7	500	5W	2700K	80+	120VAC	B11	E26	3.62/92	1.38/35	15,000
09877	LED7WA19/FIL/827-DIM-G7	800	7W	2700K	80+	120VAC	A19	E26	4.13/105	2.36/60	15,000
09441	LED7WA19/FIL/SB/827K-DIM-G7	700	7W	2700K	80+	120VAC	A19	E26	3.94/100	2.36/60	15,000

NOTE: Use order code when ordering.

DIMENSIONS

