

DATA SHEET 10190000 Valid from:

EPIC® H-BE 6 SS / H-BE 6 BS

Description

- Standard inserts with screw termination, crimp termination, cage clamp termination and Push-In termination
- The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents
- Use for railway applications -Brand protection in rail vehicles: test according to EN 45545-2. Requirement sentences R22 and R23. Hazard levels HL1, HL2 and HL3.
- UL tested for applications in the control cabinet in accordance with UL 508 / UL 2237



27.03.2017

General Characteristics

Series H-BE 6

Version Male/Female(Article 10191000)

Wire Protection Yes
Number of Contacts 6 + PE

Termination Methods Screw termination: 0.5 - 2.5 mm²

Protection (DIN EN 60529) IP65
Protection (NEMA 250, UL50E) 4, 12

Temperature Range -40°C to +100°C, short-term up to +125°C

Mechanical Characteristics

Cycle of mechanical operation 500

Electrical Characteristics

500 V Rated Voltage, IEC 600 V Rated Voltage, UL 600 V Rated Voltage, CSA Rated Impulse Voltage 6 kV Rated Current, IEC 16 A Rated Current, UL 16 A Rated Current, CSA 16 A Contact Resistance < 2 mOhm

Degree of Soiling 3

Materials and Surfaces

Contacts Copper alloy, hard silver-plated

Insulating Body PC Flammability Class according to UL 94 V0

Approvals

UL-Approval, E-File-Number E75770 VDE-Approval, VDE-REG.-Nr. B437

Standard

Product Standard IEC 61984, UL 1977


Creator: MANU2/PDP	Document: DB10190000EN	Page 1 of 2
Released: IVSE1/PDP	Version: 01	





DATA SHEET	10190000
EPIC [®] H-BE 6 SS / H-BE 6 BS	Valid from: 27.03.2017


Technical Drawings



















Robust



Temperature-resistant

Info

Multifunctional insert for versatile appliactions Screw, crimp, cage clamp and Push-In version - freely combinable

Application range

Mechanical engineering Light & sound technology Plastics industry

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANU2/PDP	Document: DB10190000EN	Page 2 of 2
Released: IVSE1/PDP	Version: 01	