

## EPIC® H-A 32 TG

Rugged housings for 2 inserts

The robust housing is intended for the installation of two inserts and subsequent placement in rectangular connectors. It can be used, for example, in control systems.

### Info

Compact, robust metal housings for double size H-A 32



Waterproof



Robust



Mechanical resistance



Industrial machinery and plant engineering

### Benefits

For two inserts of the small H-A, H-D and STA series. Space-saving

### Application range

Machine and equipment manufacturing

Control engineering

### Product features

Hood

Bolts for double lever

Straight cable entry

Versions with / without neck

Last Update (08.02.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## EPIC® H-A 32 TG

### Technical Data

|                    |                                                                                              |
|--------------------|----------------------------------------------------------------------------------------------|
| Classification:    | ETIM 5.0 Class-ID: EC000437<br>ETIM 5.0 Class-Description: Housing for industrial connectors |
| Material:          | Housing: aluminium alloy, grey<br>Lever: zinc-plated steel<br>Sealing: NBR                   |
| Protection rating: | IP 65 (latched)                                                                              |
| VDE-tested:        | UL-tested:<br>UL File Number: E75770                                                         |
| Temperature range: | -40°C to +100°C, short-term up to +125°C                                                     |

### Note

Photographs are not to scale and do not represent detailed images of the respective products.

\* Prices are net prices without VAT and surcharges. Sale to business customers.

**EPIC® H-A 32 TG**

| Article number                                                   | Article description | PG | Neck | B    | B1   | H  | L    | L1   |
|------------------------------------------------------------------|---------------------|----|------|------|------|----|------|------|
| H-A housing: hood (straight cable entry, bolts for double lever) |                     |    |      |      |      |    |      |      |
| 10582000                                                         | H-A 32 TG 21        | 21 | yes  | 56   | 70.8 | 75 | 82   | 49.6 |
| 10582001                                                         | H-A 32 TG 21        | 21 | 56   | 70.8 | 75   | 82 | 49.6 |      |
| 10583000                                                         | H-A 32 TG 29        | 29 | yes  | 56   | 70.8 | 75 | 82   | 49.6 |
| 19582000                                                         | H-A 32 TG M25       | 25 | 56   | 70.8 | 75   | 82 | 49.6 |      |
| 19583000                                                         | H-A 32 TG M32       | 32 | 56   | 70.8 | 75   | 82 | 49.6 |      |
| 79520600                                                         | H-A 32 TG M40       | 40 | 56   | 70.8 | 75   | 82 | 49.6 |      |

Last Update (08.02.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16