



Published on *Fluke Calibration: Europe* (<https://eu.flukecal.com>)

[Home](#) > [Products](#) > [Reference pressure modules](#) > [750RD5](#) > 750RD5

750RD5

Reference Dual Range Pressure Module, -15 to 30 psi (-1 to 2 bar)

Highlights

A complete family of pressure modules

A family of 48 pressure modules covers pressure calibrations from 0 to 1 in H₂O to 10,000 psi (2.5 mBar to 690 bar).

Gage pressure modules have one pressure fitting and measure the pressure with respect to atmospheric pressure. Differential pressure modules have two pressure fittings and measure the difference between the applied pressure on the high fitting versus the low fitting. Each module is clearly labeled for range, overpressure and media compatibility. All modules include NPT, metric (BSP) and M20 adapters.

Description

- 0.025 % reference uncertainty
- 6-month and 1-year specifications
- Temperature compensated 0 °C to 50 °C
- Digital communication to calibrators, no analog losses or errors
- Broad selection of ranges
- Gage, differential, dual range, absolute and vacuum measurement models

Specifications

Specifications

Parameter / Range	-15 to 30 psi (-1 to 2 bar)
Burst Rating ⁶	4X
Hi Side Media ²	Dry Air
Lo Side Media ²	N/A
Reference Uncertainty ⁴	± 0.01% of FS
Total Uncertainty 1-year (15-35 °C)	± 0.02% of FS
Total Uncertainty 1-year ¹	± 0.04% of FS
Total Uncertainty 6-month (15-35 °C)	± 0.015% of FS

Total Uncertainty 6-month1

 $\pm 0.035\%$ of FS

1. Total uncertainty, % of full span for temperature range 0 °C to +50 °C, one year interval. Total uncertainty, 1.0% of full span for temperature range -10 °C to 0 °C, one year interval. No 6 month specification available for range -10 °C to 0 °C.
2. "Non-corrosive gasses" indicates dry air or non-corrosive gas as compatible media. "Stainless Steel 316-SS" indicates media compatible with Type 316 Stainless Steel.
3. Specifications % of Full Span unless otherwise noted.
4. * Reference Uncertainty is the specification for as left data for 24 hours.
5. When reference class modules are used with fixed resolution products (717, 718, 719 series, 725 and 726) calibrators add ± 1 count to the overall accuracy specification.
6. Burst rating specification refers to the multiplier times full scale of the module for the rated burst pressure.

Models and Accessories



©1995-2023 Fluke Corporation

Source URL: <https://eu.flukecal.com/products/accessories/reference-pressure-modules/750rd5>