# Eaton GBB-30-R

## Catalog Number: GBB-30-R

Eaton GBB Series Very fast-acting fuse 30A, 250 Vac, 125 Vdc, GBB-30-R

### General specifications

Product Name Catalog Number

Eaton Bussmann series very fast-acting GBB-30-R

fuse

UPC

051712538718

EAN Product Length/Depth

5027590246811 1.25 in

Product Height Product Width

0.25 in 0.25 in

Product Weight Compliances
0.006 lb CE Marked

RoHS Compliant



### **Product specifications**

Resistance

0.00206 ohms DC cold

Fuse indicator

Non-indicating

Interrupt rating

200 AIC at 250 Vac 200 AIC at 125 Vac/dc

Type

Electronic

Connection

Ferrule end x ferrule end

Response time

2 min at 150%, 6 sec at 250%

Quantity

5

Material

Ceramic tube

Nickel-plated brass end cap construction

Voltage rating

250 Vac, 125 Vdc

Application

Electronic circuits

Amperage Rating

30 A

Voltage drop

0.0657 mV typical

#### Resources

PEP Eco-passport

EATO-00034-V01.01-EN

Specifications and datasheets

Eaton GBB ceramic tube fuses data sheet

Eaton Specification Sheet - GBB-30-R



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia