

Eaton GBB-3-R

Catalog Number: GBB-3-R

Eaton GBB Series Very fast-acting fuse 3A, 250 Vac, 125 Vdc, GBB-3-R

General specifications

Product Name	Catalog Number
Eaton Bussmann series very fast-acting fuse	GBB-3-R
	UPC
	051712549929
EAN	Product Length/Depth
5027590246699	1.25 in
Product Height	Product Width
0.25 in	0.25 in
Product Weight	Compliances
0.006 lb	CE Marked
	RoHS Compliant



Product specifications

Resistance

0.04475 ohms DC cold

Fuse indicator

Non-indicating

Interrupt rating

200 AIC at 250 Vac

10 kAIC at 125 Vac/dc

Type

Electronic

Connection

Ferrule end x ferrule end

Response time

2 min at 150%, 1 sec at 250%

Quantity

5

Material

Ceramic tube

Nickel-plated brass end cap construction

Voltage rating

250 Vac, 125 Vdc

Application

Electronic circuits

Amperage Rating

3 A

Voltage drop

0.1816 mV typical

Resources

PEP Eco-passport

[EATO-00034-V01.01-EN](#)

Specifications and datasheets

[Eaton Specification Sheet - GBB-3-R](#)

[Eaton GBB ceramic tube fuses data sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)