



Representative

Catalog Number: **SGAC 250**
Product ID: 7TAA262900R0008
UPC Number: 78378675156
Status: Active

Aluminum Multi-Range Dieless Compression Splices - Minimum Tension, conductor size 4 sol.-266.8 - 4/0 ACSR., decimal range min outside diameter .128, decimal range max outside diameter .470, tool - VC-5/VC-6, length 4 in

UNSPSC Specifications

| | |
|------------------|---|
| UNSPSC | 39121449 Wire or cable compression splice |
| IGCC | 4669 Wire or cable compression splice |
| Brand Name | Blackburn |
| Type | Aluminum Multi-Range Dieless Compression Splice |
| Special Features | Dual-rated. Use with Aluminum and Copper conductors. All splices are marked with conductor size for easy identification. Solid center stop ensures proper cable insertion. Connector Bores coated with Oxide Inhibitor and Capped to Prevent Oxidation. Made from Aluminum for high strength and high conductivity. |
| Size | 4 inches long |
| Connection | Crimp/Compression |
| Conductor Range | #4 Solid - 266.8 - 4/0 ACSR |
| Material | Aluminum |
| Insulation | Non-Insulated |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 100 |
| Outer Dimensions (inches) | 13.5x8.6x8.4 |
| Weight Uom | 0.17 lbs. Each |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| SDS US 1 | sds-00042-tb2 |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com