

Catalog Number: USK 2/0
Product ID: 7TAA260100R0009
UPC Number: 78378675556
Status: Active



Actual

Aluminum Flood-Seal Mechanical Splice Two-Wire Kits, conductor range 14-2/0 connector length 1-1/2 inch, slotted screw, screws per side 1

UNSPSC Specifications

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Homac
Type	Mechanical Splice
Special Features	Prefilled with Oxide Inhibitor to prevent Oxidation and keep out Moisture. Dual-Rated and approved for use with Aluminum and Copper Conductors. EPDM Rubber Splice Covers ensure a fully insulated, watertight repair splice. No Taping, Heat-Shrink or Mastic needed.
Application	Repair Splice
Size	1-1/2 inch connector
Connection	Mechanical
Conductor Range	14 to 2/0
Number Of Conductors	2
Material	Aluminum Connector, EPDM Cover
Insulation	Yes

Packaging

Outer Quantity	25
Outer Dimensions (inches)	18x8x7.5
Weight Uom	19 lbs. per 100

Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com