


Straight Blade Devices


15 and 20 Ampere, 125 Volts

SNAPConnect®


Extra Heavy Duty Receptacles




Duplex	Color	Catalog Number	
Specification grade, finder groove, nylon face, modular receptacle which requires pigtailed connector on page A-13.	Black	SNAP5262BKA	SNAP5362BKA
	Brown	SNAP5262A	SNAP5362A
	Gray	SNAP5262GYA	SNAP5362GYA
	Ivory	SNAP5262IA	SNAP5362IA
	Light Almond	SNAP5262LAA	SNAP5362LAA
	Red	SNAP5262RA	SNAP5362RA
Specification grade, smooth, nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	White	SNAP5262WA	SNAP5362WA
	Black	SNAP5262BKNA	SNAP5362BKNA
	Brown	SNAP5262NA	SNAP5362NA
	Gray	SNAP5262GYNA	SNAP5362GYNA
	Ivory	SNAP5262INA	SNAP5362INA
	Light Almond	SNAP5262LANA	SNAP5362LANA
Specification grade, Tamper-Resistant, smooth nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	Red	SNAP5262RNA	SNAP5362RNA
	White	SNAP5262WNA	SNAP5362WNA
Specification grade, Tamper-Resistant, Split Circuit, smooth nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	Black	SNAP5262BKTR	SNAP5362BKTR
	Blue	SNAP5262BLTR	SNAP5362BLTR
	Brown	SNAP5262TR	SNAP5362TR
	Gray	SNAP5262GYTR	SNAP5362GYTR
	Ivory	SNAP5262ITR	SNAP5362ITR
	Light Almond	SNAP5262LATR	SNAP5362LATR
Isolated ground ^A , Specification grade, Tamper-Resistant.	Red	SNAP5262RTR	SNAP5362RTR
	White	SNAP5262WTR	SNAP5362WTR
Specification grade, Tamper-Resistant, Split Circuit, smooth nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	Black	SNAP5262BKSCTR	SNAP5362BKSCTR
	Blue	SNAP5262BLSCTR	SNAP5362BLSCTR
	Brown	SNAP5262SCTR	SNAP5362SCTR
	Gray	SNAP5262GYSCTR	SNAP5362GYSCTR
	Ivory	SNAP5262ISCTR	SNAP5362ISCTR
	Light Almond	SNAP5262LASCTR	SNAP5362LASCTR
Isolated ground ^A , Specification grade, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	Red	SNAP5262RSCTR	SNAP5362RSCTR
	White	SNAP5262WSCTR	SNAP5362WSCTR
Isolated ground ^A , Specification grade, with Power Indicating LED.	Black	SNAP5262IGTR	SNAP5362IGTR
	Black	SNAP5262BKL	SNAP5362BKL
	Blue	SNAP5262BLL	SNAP5362BLL
	Brown	SNAP5262L	SNAP5362L
	Gray	SNAP5262GYL	SNAP5362GYL
	Ivory	SNAP5262IL	SNAP5362IL
Specification grade, Tamper-Resistant, with Power Indicating LED, smooth nylon face, modular receptacle which requires pigtailed connector on page A-13. Assembled in USA.	Light Almond	SNAP5262LAL	SNAP5362LAL
	Red	SNAP5262RL	SNAP5362RL
	White	SNAP5262WL	SNAP5362WL
Isolated ground ^A , Specification grade, with Power Indicating LED.	Orange	SNAP5262IGL	SNAP5362IGL
	Black	SNAP5262BKLTR	SNAP5362BKLTR
	Blue	SNAP5262BLLTR	SNAP5362BLLTR
	Brown	SNAP5262LTR	SNAP5362LTR
	Gray	SNAP5262GYLTR	SNAP5362GYLTR
	Ivory	SNAP5262ILTR	SNAP5362ILTR
Isolated ground ^A , Specification grade, TR with Power Indicating LED.	Light Almond	SNAP5262LALTR	SNAP5362LALTR
	Red	SNAP5262RLTR	SNAP5362RLTR
	White	SNAP5262WLTR	SNAP5362WLTR
	Orange	SNAP5262IGLTR	SNAP5362IGLTR




SNAP5362IA




SNAP5362LA-



SNAP5362L



SNAP5362GYLTR



SNAP5261I

Dimensions in Inches (mm)

SNAPConnect® Extra Heavy Duty Standard Single Receptacles

Color	Standard Duplex		Standard Duplex Tamper-Resistant	
	15A 125V	20A 125V	15A 125V	20A 125V
Black	SNAP5261BK	SNAP5361BK	SNAP5261BKTR	SNAP5361BKTR
Blue	SNAP5261BL	SNAP5361BL	SNAP5261BLTR	SNAP5361BLTR
Brown	SNAP5261	SNAP5361	SNAP5261TR	SNAP5361TR
Gray	SNAP5261GY	SNAP5361GY	SNAP5261GYTR	SNAP5361GYTR
Ivory	SNAP5261I	SNAP5361I	SNAP5261ITR	SNAP5361ITR
Light Almond	SNAP5261LA	SNAP5361LA	SNAP5261LATR	SNAP5361LATR
Red	SNAP5261R	SNAP5361R	SNAP5261RTR	SNAP5361RTR
White	SNAP5261W	SNAP5361W	SNAP5261WTR	SNAP5361WTR