

KEL-U 24

Cable entry frames



V2A
anti-corrosive

Also available with stainless steel screws (V2A).



Also available with threaded bushings.



Slit KT grommets



Description	Type	Order No.	Grommets small large	PU
-------------	------	-----------	---------------------------	----

Product description

Split cable entry system for routing cables with connectors providing an IP54 / up to NEMA type 12 rating. Routing, sealing and providing strain relief for cable diameters from 1 to 35 mm. The new cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly. The KEL-U 24 frame matches exactly the cut-out dimensions for 24-pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. A flat rubber gasket is included in the shipment.

Advantages & benefits




- Fast and easy assembly
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of cable grommets (certified acc. to EN 60529)
NEMA type rating	NEMA type 12 (acc. to UL 50E)
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	36/46 × 112 mm / page 200 - 201
Frame depth	17 mm

Accessories

Cable grommets	44 - 48
KEL-SNAP Mounting frames	31
KEL-EMC Cable collectors	126 - 128
KDR Base plates	146 - 153
FP Flange plates	160 - 165
MP Module plates	156 - 157
ST Plugs	49

	KEL-U 24 10 KEL-U 24 10 with V2A screws	54241 54241.200	10 - 10 -	10 10
	KEL-U 24 7 KEL-U 24 7 with V2A screws	54247 54247.200	6 1 6 1	10 10
	KEL-U 24 4 KEL-U 24 4 with V2A screws	54244 54244.200	2 2 2 2	10 10