



## Main

Product or component type	Coil
Accessory / separate part destination	Class 8903 contactor

## Complementary

[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	170 VA 180 VA
Average consumption	35 VA
Height	2.38 in (60.5 mm)
Width	2.11 in (53.6 mm)
Maximum Depth	1.46 in (37.1 mm)

## Ordering and shipping details

Category	21756 - 9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	00785901081289
Nbr. of units in pkg.	1
Package weight(Lbs)	0.36 lb(US) (0.16 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	2.20 in (5.588 cm)
Package 1 width	2.70 in (6.858 cm)
Package 1 Length	3.40 in (8.636 cm)

## Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.