

UT2R2122B

Meter socket, horizontal ganged, ringless socket, 205A, 2 position, 4 jaws, 600 VAC max, overhead/underground, no bypass



Main

Product Type	Meter Socket
Rated Current	205 A
Number of Meter Sockets	2
Number of Phases	1 phase
Rated Operational Voltage	600 V AC

Complementary

Number of Jaws	4 without jaw release
Bypass Type	No bypass
Meter Socket Type	Ringless
Certifications	UL Listed
Enclosure Rating	NEMA 3R
Box Number	17R
Wire Gauge	AWG 6...250 kcmil aluminium)main lugs AWG 6...250 kcmil copper)main lugs AWG 8...AWG 2/0 aluminium)branch lugs AWG 8...AWG 2/0 copper)branch lugs
Service Feed Location	UG OH
Wiring Configuration	3-wire
Hub Type	A ACP closing plate

Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	00785901291244
Nbr. of units in pkg.	1
Package weight(Lbs)	27.3 lb(US) (12.38 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.50 in (16.51 cm)
Package 1 width	15.00 in (38.1 cm)
Package 1 Length	25.00 in (63.5 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	24
Package 2 Weight	684.00 lb(US) (310.257 kg)
Package 2 Height	43.50 in (110.49 cm)

Package 2 width	42.00 in (106.68 cm)
Package 2 Length	42.00 in (106.68 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------