

Type PG Armored/Metal Clad Cable Connectors

For Jacketed Metal Clad Cable

NEC/CEC:
Listed for Ordinary Locations

Applications

- Use with jacketed armored cable.
- To terminate and ground the armor, and to secure and seal cable entrance into a cabinet or terminal box through a standard knockout, slip-hole or DandT entrance.

Features

- Suitable for wet locations
- Gland type (with grounding sleeve and set-screws)

Standard Materials

- **Type PG** - malleable or ductile iron.
- They are supplied with electro-plated grounding screws and pressure ring.
- They are available with stainless steel grounding screws and pressure ring. Contact your local representative for price and availability.

Standard Finishes


- Fittings - zinc plated

Options


- All fittings can be supplied with neoprene gasket, locknut and insulating bushing. (Add Suffix **-LGB.**) Contact your local representative for price and availability.

NEC/CEC Certifications and Compliances

- UL Standard: ANSI/UL 514B
- UL Listed: E-36853
- CSA Standard: C22.2 No.18
- CSA Certified: 15553
- Suitable for wet locations
- Fed. Spec: W-F-406B



Type PG



Size (Inches)	Cable Range Dia. Over Jacket			Dimensions in Millimeters (Inches)			Malleable Iron Catalog Number
	Min.	Max.	Max Dia.	B Approx.	C	Dia. of Cable Core	
1/2	12.19 (0.48)	14.48 (0.57)	39.62 (1.56)	63.50 (2.50)	14.22 (0.56)	7.87 (0.31)	PG-57-05
1/2	14.48 (0.57)	16.76 (0.66)	39.62 (1.56)	63.50 (2.50)	14.22 (0.56)	10.16 (0.4)	PG-66-05
1/2	16.26 (0.64)	19.81 (0.78)	39.62 (1.56)	63.50 (2.50)	14.22 (0.56)	12.95 (0.51)	PG-78-05
1/2	19.05 (0.75)	22.61 (0.89)	39.62 (1.56)	63.50 (2.50)	14.22 (0.56)	15.49 (0.61)	PG-89-05
1/2	21.59 (0.85)	24.89 (0.98)	39.62 (1.56)	63.50 (2.50)	14.22 (0.56)	15.49 (0.61)	PG-98-05
3/4	19.05 (0.75)	22.61 (0.89)	49.28 (1.94)	66.80 (2.63)	14.22 (0.56)	15.49 (0.61)	PG-89-07
3/4	21.59 (0.85)	24.89 (0.98)	49.28 (1.94)	66.80 (2.63)	14.22 (0.56)	18.29 (0.72)	PG-98-07
3/4	22.35 (0.88)	27.18 (1.07)	49.28 (1.94)	66.80 (2.63)	14.22 (0.56)	19.56 (0.77)	PG-107-07
3/4	26.16 (1.03)	30.73 (1.21)	49.28 (1.94)	66.80 (2.63)	14.22 (0.56)	21.59 (0.85)	PG-121-07
1	22.35 (0.88)	27.18 (1.07)	58.67 (2.31)	77.72 (3.06)	17.53 (0.69)	19.05 (0.75)	PG-107-10
1	26.16 (1.03)	30.73 (1.21)	58.67 (2.31)	77.72 (3.06)	17.53 (0.69)	23.11 (0.91)	PG-121-10
1	29.97 (1.18)	35.05 (1.38)	58.67 (2.31)	77.72 (3.06)	17.53 (0.69)	26.42 (1.04)	PG-138-10
1-1/4	29.97 (1.18)	35.05 (1.38)	71.37 (2.81)	85.85 (3.38)	17.53 (0.69)	26.42 (1.04)	PG-138-12
1-1/4	34.54 (1.36)	41.40 (1.63)	71.37 (2.81)	85.85 (3.38)	17.53 (0.69)	31.50 (1.24)	PG-163-12
1-1/4	41.15 (1.62)	47.75 (1.88)	71.37 (2.81)	85.85 (3.38)	17.53 (0.69)	36.07 (1.42)	PG-188-12
1-1/2	43.94 (1.73)	50.80 (2.00)	79.50 (3.13)	101.60 (4.00)	19.05 (0.75)	40.89 (1.61)	PG-200-15
1-1/2	49.02 (1.93)	55.63 (2.19)	79.50 (3.13)	101.60 (4.00)	19.05 (0.75)	40.89 (1.61)	PG-219-15
2	49.02 (1.93)	55.63 (2.19)	100.08 (3.94)	109.47 (4.31)	19.81 (0.78)	45.47 (1.79)	PG-219-20
2	53.34 (2.1)	60.96 (2.4)	100.08 (3.94)	109.47 (4.31)	19.81 (0.78)	49.78 (1.96)	PG-240-20
2	59.69 (2.35)	66.29 (2.61)	100.08 (3.94)	109.47 (4.31)	19.81 (0.78)	53.09 (2.09)	PG-261-20
2	63.50 (2.50)	69.85 (2.75)	100.08 (3.94)	109.47 (4.31)	19.81 (0.78)	53.09 (2.09)	PG-275-20
2-1/2	60.20 (2.37)	66.80 (2.63)	117.60 (4.63)	133.35 (5.25)	30.23 (1.19)	50.55 (1.99)	PG-263-25
2-1/2	65.02 (2.56)	71.88 (2.83)	117.60 (4.63)	133.35 (5.25)	30.23 (1.19)	61.72 (2.43)	PG-283-25
2-1/2	69.34 (2.73)	76.20 (3.00)	117.60 (4.63)	133.35 (5.25)	30.23 (1.19)	61.72 (2.43)	PG-300-25
2-1/2	75.44 (2.97)	81.79 (3.22)	117.60 (4.63)	133.35 (5.25)	30.23 (1.19)	63.25 (2.49)	PG-322-25
3	69.34 (2.73)	76.20 (3.00)	131.83 (5.19)	136.65 (5.38)	31.75 (1.25)	61.72 (2.43)	PG-300-30
3	74.68 (2.94)	81.79 (3.22)	131.83 (5.19)	136.65 (5.38)	31.75 (1.25)	63.25 (2.49)	PG-322-30
3	81.28 (3.2)	88.14 (3.47)	131.83 (5.19)	136.65 (5.38)	31.75 (1.25)	77.47 (3.05)	PG-347-30
3	85.60 (3.37)	92.20 (3.63)	131.83 (5.19)	136.65 (5.38)	31.75 (1.25)	77.47 (3.05)	PG-363-30
3-1/2	85.60 (3.37)	92.20 (3.63)	149.35 (5.88)	141.22 (5.56)	31.75 (1.25)	81.03 (3.19)	PG-363-35
3-1/2	91.19 (3.59)	98.55 (3.88)	149.35 (5.88)	141.22 (5.56)	31.75 (1.25)	86.11 (3.39)	PG-388-35
3-1/2	97.03 (3.82)	104.14 (4.10)	149.35 (5.88)	141.22 (5.56)	31.75 (1.25)	90.17 (3.55)	PG-410-35
4	96.52 (3.80)	104.14 (4.10)	162.05 (6.38)	143.00 (5.63)	33.27 (1.31)	91.19 (3.59)	PG-410-40
4	101.60 (4.00)	108.71 (4.28)	162.05 (6.38)	143.00 (5.63)	33.27 (1.31)	96.27 (3.79)	PG-428-40
4	106.68 (4.20)	113.54 (4.47)	162.05 (6.38)	143.00 (5.63)	33.27 (1.31)	101.35 (3.99)	PG-447-40
4	111.76 (4.40)	118.11 (4.65)	162.05 (6.38)	143.00 (5.63)	33.27 (1.31)	104.39 (4.11)	PG-465-40