



Note:  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:  
**JDL26200**



Schneider Electric United States  
 North American Division  
 Boston One Campus  
 800 Federal Street  
 Andover, MA 01810, USA  
 Phone: +1 8773425173  
 Email: CCC@us.schneider-electric.com

Technical Information:

General Application: Provides overload and short circuit protection  
 For Use With: Industrial Enclosures and Switchboards  
 Approvals: UL Listed - CSA Certified - IEC Rated  
 Mounting Type: Unit Mount  
 Terminal Type: Line: Lug - Load: Lug  
 Wire Size: #3/0-350 AWG/kcmil(Al/Cu)  
 Weight: 5 Pounds  
 Depth: 5.00 Inches  
 Height: 7.52 Inches  
 Width: 4.12 Inches

Description: PowerPact J-frame Thermal Magnetic Circuit Breaker  
 Number of Poles: 2-Pole  
 Ampere Rating: 200A  
 Voltage Rating: 600VAC/250VDC  
 Interrupting Rating: 25kA at 240VAC - 18kA at 480VAC - 14kA at 600VAC - 20kA at 250VDC  
 Circuit Breaker Rating: 80% Rated  
 Fixed AC Magnetic Trip: Low: 1000A - High: 2000A

Specification: