



### Main

Product or Component Type	Circuit breaker
Range	PowerPact P
Current Sensor Rating Range	1200 A
Rated Current	1200 A
Breaking Capacity	65 KA 240 V AC 35 KA 480 V AC 18 kA 600 V AC
Trip Unit Technology	Electronic, basic, ET 1.0I, LI
AWG Gauge	AWG 3/0...500 kcmil aluminium/copper)4

### Complementary

Certifications	IEC CSA UL Listed
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Bolt-on
Mounting Mode	Unit mount
Poles Description	3P
Circuit Breaker Rating Code	G
Continuous Current Rating	80 %
Electrical Connection	Lugs load Lugs line
Tightening Torque	442.54 Lbf.in (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m)
Height	16.16 in (410.46 mm)
Width	8.27 in (210.06 mm)
Depth	8.05 in (204.47 mm)

### Ordering and shipping details

Category	01215 - PG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
GTIN	00785901446453
Nbr. of units in pkg.	1
Package weight(Lbs)	37.58 lb(US) (17.05 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Package 1 Height	14.50 in (36.830 cm)
Package 1 width	14.60 in (37.084 cm)
Package 1 Length	22.50 in (57.150 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------