



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]
 - Inch Dimensions are derived from the metric.

Part No.:
ATS22D88S6U

Schneider Electric
 Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

Control Voltage: 110 Vac (-15% to 10%)
 Logic Input: 3
 Analog Input: 1 PTC probe
 Analog Output: N/A
 Logic/Relay Output: 2 (N/C / NO)
 Communication: Modbus
 Weight [lb]/[kg]: 17.2/7.8
 UL File No.: E184727
 CSA File: 224330
 Other: UL, CSA, CE, GOST, C-Tick, CCC and RoHS

Specification:

Description: Soft Start
 Family: Altistart 22
 Product Line: Soft Starters
 Application: Constant & Variable Torque
 Output Ampere Rating: 88
 Max. HP Rating 208V: 25
 Max. HP Rating 230V: 30
 Max. kW Rating 400V: 37
 Max. HP Rating 460V: 60
 Max. HP Rating 575V: 75
 Enclosure Rating: IP20 (IP00 if no connections)
 Frame Size: B