

W5461-T0W

Weather- and Tamper-Resistant Single Receptacle, 20 Amp 250 Volt, White

Single Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Weather- and Tamper-Resistant, Smooth Face, 20 Amp, 250 Volt, Back and Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - White


Leviton's 250 Volt Tamper-Resistant Receptacles are the industry's first and only solution to the revisions of the NEC Article 406.12! These weather-resistant single receptacles also provide compliance for Article 406.9 of the National Electrical Code (NEC) for wet and damp locations and include added protection against corrosion, UV degradation and cold impact damage.

- Accommodates back and side wiring
- Nickel-plated steel strap maximizes corrosion resistance
- Brass-self grounding clip is permanently staked on for secure and reliable performance
- Common applications: education facilities, commercial buildings, health care facilities, hospitality, and multiple dwelling units (MDUs)



UPC Code : 078477101728

Country Of Origin : Mexico



Available Colors :



Technical Information

Electrical Specifications

Amperage : 20 A
Dielectric Voltage : 2000 VAC
Grounding : Self-Grounding
HP Rating : 2 HP
Pole : 2
Temperature Rise : Max 30 C
Voltage : 250 VAC
Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94
Operating Temperature : Maximum Continuous 75°C, minimum -40°C (w/o impact)

Material Specifications

Body Material : Nylon
Face Material : PBT
Ground Contacts : Phosphor Bronze
Grounding Screw : #8 Brass
Line Contacts : Brass Triple Wipe 0.040"
Mounting Screws : #6 Stainless Steel

Mounting Strap : Nickel-Plated Steel

Tamper Resistant Shutter Mechanism : Thermoplastic

Terminal Clamps : Brass

Terminal Screws : #10 Brass

Mechanical Specifications

Product ID : Ratings are Marked on Device

Strap Construction :

Terminal Accom. : #14-#10 AWG Solid or Stranded

Termination : Back & Side Wire

Product Features

Color : White

Device Type : Single Receptacle Outlet

Feature : Weather- and Tamper-Resistant , Smooth Face , RoHS Compliant

Grade : Heavy-Duty Industrial Specification Grade

NEMA : 6-20R

Standards & Certifications

NEMA Rating : WD-1 and WD-6

Standards and Certifications : UL 498; CSA C22.2, No. 42; Fed Spec WC-596; NOM

Warranty

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

