

DG280A TWO CHANNEL 24 HOUR DUTY CYCLE AND SIGNAL TIMER

APPLICATIONS



Ideal for repeating processes or manufacturing control. Able to alternate patterns over 31 days.



FEATURES

- Daily setting: 56 events
- Day cycle patterns: Can set timer to repeat daily events from 1 day to 31 days in a row then skip operation for 1 day to 31 days
- Alternate Operations: Each channel can be set to operate on opposite days
- Automatic input voltage detection
- Capacitor provides minimum of 1 week of real time backup for program and time of day

SPECIFICATIONS

MULTI-VOLTAGE INPUT:
120-277VAC, 50/60Hz
OPERATING TEMPERATURE:
-31 °F to 131 °F (-35 °C to 55 °C)
ENCLOSURE:
Noryl Indoor/Outdoor NEMA 3R

**UNIQUE
PROBLEM
SOLVER!**

**AN INDUSTRY
FIRST!**



CAUTION: Before wiring and servicing, power to this time switch and the equipment it controls must be turned off at the main panel. Lining off the control's manual switch only will not prevent a shock hazard. Replace this insulator after wiring.

AVERTISSEMENT: Avant de procéder à l'installation électrique ou à son entretien, le courant de l'interrupteur de la minuterie et de l'équipement qu'il contrôle doit être débranché uniquement l'interrupteur de commande manuel. Remettre cet isolateur en place une fois le câblage terminé.

PRECAUCION: Antes de conectar o dar servicio a este aparato se debe desconectar primero, así como del equipo que controla. Apagando el control manual del interruptor, no previene una descarga eléctrica. Favor de colocar este paraincisor en su lugar después de realizar las operaciones de cableado.

RATINGS

CONTACTS NO:
20A Resistive @ 24-277VAC
20A Ballast @ 120-277VAC
15A Tungsten @ 120VAC
720VA Pilot Duty @ 120-277VAC
1HP Motor @ 120VAC
2HP Motor @ 277VAC
20A Resistive @ 28VDC

CONTACTS NC:
10A Resistive @ 24-277VAC
10A Ballast @ 120-277VAC
Tungsten @ 120VAC
290-360VA Pilot Duty @ 120-277VAC
1/4HP Motor @ 120VAC
1/2HP Motor @ 277VAC
10A Resistive @ 28VDC

