



### Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

### Complementary

Line Rated Current	50 A
Number of Poles	1P
Interrupt Rating	10 KA 120/240 V AC 10 KA 120 V AC 5 kA 48 V DC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 120 V AC 48 V DC
Mounting mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminium/copper
Maximum Height	4.05 in (102.87 mm)
Maximum Depth	2.95 in (74.93 mm)
Maximum Width	0.75 in (19.05 mm)
Tightening torque	45 lbf.in (5.08 N.m) AWG 14...AWG 2)

### Environment

Product certifications	IEC UL Listed CSA
------------------------	-------------------------

### Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901418627
Nbr. of units in pkg.	40
Package weight(Lbs)	0.36 lb(US) (0.16 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	1.00 in (2.540 cm)
Package 1 width	3.10 in (7.874 cm)
Package 1 Length	4.50 in (11.430 cm)


## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions



2.50 [64] MIN. WIRE BENDING SPACE FOR 2 AWG  
1.50 [38] MIN. WIRE BENDING SPACE FOR 14 AWG  
TYP. BOTH ENDS FOR ALL CB'S SHOWN PER ARTICLE 430-1-(B) NEC

