

Product data sheet

Characteristics

HOM24L70F

Load center, Homeline, 1 phase, 2 spaces, 4 circuits, 70A fixed main lugs, NEMA1, flush cover



Main

Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	Main lugs
Rated Current	70 A
Number of Spaces	2
Number of Circuits	4
Enclosure Rating	NEMA 1 indoor NEMA 3R outdoor
Cover Type	Flush cover
Electrical Connection	Lugs

Complementary

Short Circuit Current Rating	10 kA
Number of Tandem Breakers	2
Number of Phases	1 phase
Rated Operational Voltage	120/240 V AC
Wire Size	AWG 12...AWG 3 aluminium AWG 14...AWG 4 copper
Wiring Configuration	3-wire
Cover Finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel Gray
Box Number	2
Height	9.29 in (236 mm)
Width	4.80 in (122 mm)
Depth	3.19 in (81 mm)

Environment

Ambiant Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL E-6294

Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901061151
Nbr. of units in pkg.	1
Package weight(Lbs)	3.79 lb(US) (1.72 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	4.10 in (10.414 cm)
Package 1 width	6.60 in (16.764 cm)
Package 1 Length	11.40 in (28.956 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	Lifetime
----------	----------