

Rittal – The System.

Faster – better – everywhere.

Cast aluminum housing GA – GA 9117.210

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Cast aluminum housing GA – GA 9117.210

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Housing: Cast aluminum
Cover: cast aluminum, all-round CR foam rubber round core seal

Surface finish: Textured paint

Color: RAL 7001

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4

IK code: IK08

Supply includes: Housing with cover
Cover screws, captive
Screws for attaching support rails
Screw for connection of the PE conductor

Product modification: Starting in September 2016, the cast aluminum housing will be delivered in an optimized design
Your advantage: The KL wall brackets can be used for wall mounting of the cast aluminum housing (1590000 and 1594000)
The enclosures have a Rittal logo on the lid and carry the CE label

Base material: Cast aluminum

Product features

Dimensions: Height: 232 mm (9.1 ")

Width: 280 mm (11 ")
Depth: 111 mm (4.4 ")

Packaging unit:	1 pc(s).
Weight/packaging unit:	3.22 kg (7.1 lb.)
EAN:	4028177145474
Customs tariff number:	85389099
ETIM 6.0:	EC000261
ETIM 5.0:	EC000058
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	GA Cast aluminium enclosure, WHD: 280x232x111 mm, Cast aluminum, without mounting plate, with cover
Approvals	
Certificates:	IK-Code Protection category
Declarations:	Declaration of conformity