Product data sheet
Characteristics

8910DPA92V09
Contactor, Definite Purpose, 90A, 2 pole, 20 HP at 230 VAC, 1 phase, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open

Main

Product or component type	Definite Purpose Contactor
Line Rated Current	90 A
Number of Poles	2P
Pole contact composition	2 NO
Range of product	DPA

Complementary

Maximum Horse Power Rating	7.5 Hp 115 V AC, 1 phase 20 hp 230 V AC, 1 phase
Locked rotor rated current	540 A 277 V AC 450 A 460 V AC 360 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	1 phase
Electrical connection	Quick connect terminals Box lugs

Environment

Product certifications	UL Recognized CSA

Ordering and shipping details

Category	21349 - 8910 DPA 9_(90 AMP)
Discount Schedule	CP1B
GTIN	00785901024552
Nbr. of units in pkg.	1
Package weight(Lbs)	3.36 lb(US) (1.52 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Package 1 Height	6.10 in (15.494 cm)
Package 1 width	6.60 in (16.764 cm)
Package 1 Length	7.10 in (18.034 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months