

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure Stainless steel – WM 8017.615

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure Stainless steel – WM 8017.615 - WM363008N4

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material: Door: Stainless steel, all-round foamed-in PU seal
Housing and door: Stainless steel 1.4301 (AISI 304)
Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with door(s)
Left hand hinge
Mounting plate
Wall mounting blind-nuts

Product features

Dimensions: Height: 900 mm (35 ")
Width: 760 mm (30 ")
Depth: 210 mm (8.3 ")

Material thickness:: Housing: 2 mm (0.08 ")
Door: 2 mm (0.08 ")
Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 870 mm (34 ")
Width: 704 mm (28 ")

Lock version:	Quarter turn
Packaging unit:	1 pc(s).
Weight/packaging unit:	50 kg (110.2 lb.)
EAN:	83191
Approvals	
Approvals:	UL + C-UL