





**UPC Code :** 078477979310

**Country Of Origin :** Please Contact Customer Service.



**Available Colors :**



## T5635-T

30W (6A) USB Dual Type-C/C Power Delivery Wall Outlet Charger with 15A Tamper-Resistant Outlet

15 Amp, 125 Volt, Decora Tamper-Resistant Outlet. NEMA 5-15R, 30W (6 Amps), Dual Type-C/C Power Delivery USB Chargers, Grounding, Side Wired & Back Wired - Light Almond

- **POWERFUL** – 30W charge on a single port. Up to 2x the charging power with PD-enabled devices
- **INNOVATIVE** – USB Type-C or USB-C provides faster charging and is emerging as the standard port on many phones, tablets and laptops
- **ENHANCED SAFETY** – Overcurrent protection helps protect electronic devices from over charging/heating and tamper-resistant outlets prevent unwanted objects from being inserted into the outlets
- **FAST CHARGING** – Smart chip ensures each device gets the power level it needs to charge fast and efficiently

### Technical Information

#### Standards and Certifications

**Amperage :** 15 A  
**FCC Part 15 :** Class B  
**Grounding :** Grounding  
**Horsepower Rating :** 15A-1/2 HP  
**Listed :** cCSAus  
**NOM :** 057  
**Ratings :** 15A-125V  
**UL 1310 :** Yes  
**UL 498 :** Yes  
**Voltage :** 125 VAC  
**Warranty :** 5-Year Limited

#### Product Features

**Amperage :** 15 A  
**Brand :** Decora  
**Color :** Light Almond  
**Flammability :** Rated V-0 per UL 94  
**Grade :** Residential/Commercial Specification Grade  
**NEMA :** 5-15R  
**Operating Temperature :** -10°C to 40°C  
**Product Type :** Outlet/USB Combo  
**Type :** Type C/C with PD Duplex Receptacle  
**Voltage :** 125 VAC  
**Wallplate :** Not Included

#### Electrical Specifications

**Amperage :** 15 A  
**Body Material :** Thermoplastic  
**Color :** Light Almond

**Cover Material :** Thermoplastic

**Grounding :** Grounding

**Horsepower Rating :** 15A-1/2 HP

**Ratings :** 15A-125V

**Strap Material :** Steel

**Voltage :** 125 VAC

#### Environmental Specifications

**Flammability :** Rated V-0 per UL 94  
**Operating Temperature :** -10°C to 40°C

**Product ID :** Stamped on Strap

**Terminal Accom. :** 14-12 AWG

**Terminal ID :** Brass-Hot Black-Hot White-Neutral Green-Gnd

**Termination :** Back & Side

**Torque Range :** 12-14 inch pounds

#### Material Specifications

**Body Material :** Thermoplastic

**Color :** Light Almond

**Cover Material :** Thermoplastic

**Grade :** Residential/Commercial Specification Grade

**Strap Material :** Steel

#### Mechanical Specifications

**Listed :** cCSAus

**NOM :** 057

**Product ID :** Stamped on Strap

**Terminal Accom. :** 14-12 AWG

**Terminal ID :** Brass-Hot Black-Hot White-Neutral Green-Gnd

**Termination :** Back & Side

**Torque Range** : 12-14 inch pounds

**Warranty** : 5-Year Limited

### **Features and Benefits**

- The most advanced USB in-wall charger on the market with up to 2X the charging power with PD-enabled devices (No data transfer capability)
- Up to 30W charge when PD-enabled device connected to single port. Up to 15W charge per port (30W total) when both USB ports are connected to devices. Examples of maximum charging outputs are: Single port connected to PD-enabled device: 15VDC@2A (30W) or 9VDC@3A (27W) Single port connected to non-PD device: 5VDC@3A (15W) Both ports connected to devices (PD or non-PD): 5VDC@3A each (up to 30W total)
- Charges most Type-C devices as well as Type A devices (adapter required)
- Shallowest profile on the market for ease of installation
- Smart chip recognizes and optimizes the charging requirements of individual devices
- Built-in overcurrent protection helps protect the electronics from receiving too much power, which can damage the device
- Internal thermo regulator prevents the electronics from overheating
- USB Ports tested to meet the industry requirement to withstand over 10,000 insertions
- Compatible with USB 3.1, 3.0, 2.0, 1.1 devices
- Type-C USB Ports enable cables to be inserted in either direction
- Tamper-Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
- Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more
- Compatible with Decora® wallplates and Decora Plus™ screwless wallplates.  
Wallplate sold separately

### **Patents\***

CA2621644	US7820909
CA2624409	US7868719
CA2677283	US8242362
CN200880004760.2	US8944859
MX338817	US9368982
US7355117	US9496726

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

