

Product data sheet

Characteristics

8911DPSO53V02

Starter, Definite Purpose, nonreversing, 50A,
3 pole, 3 phase, 120 VAC coil, melting alloy
overload, open style



Main

Product	Definite Purpose Starter
Ampere Rating	50 A
Horsepower Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase

Complementary

Enclosure Rating	Not rated (open device)
Locked Rotor Amperes	300 A 230 V AC 250 A 460 V AC 200 A 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901192541
Nbr. of units in pkg.	1
Package weight(Lbs)	2.98 lb(US) (1.35 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Package 1 Height	5.30 in (13.462 cm)
Package 1 width	4.80 in (12.192 cm)
Package 1 Length	8.30 in (21.082 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------