Where to Buy | Contact Us | EliteNet

home products services markets resources your business

Buy Online! | My Cart

Search Parameters:
<u>e-Catalog</u> > <u>Circuit Breakers.</u> > Molded Case Circuit Breakers Circuit Breakers, Molded Case Circuit Breakers

Product #: TED134015WL

Short Description: 3 POLE 480VAC 15A BREAKER

Print This Page Email This Page

SPECIFICATIONS

| Category | Thermal Magnetic |
|---------------------------------|---|
| Product Line | Thermal Magnetic |
| Trip Style | Non-Interchangeable |
| Frame Type | E150 |
| Amperage | 15A |
| Poles | 3 |
| System Voltage | 120 Vac , 120/240 Vac , 125 Vdc , 240 Vac , 250 Vdc , 277 Vac , 480 Vac |
| 120 Vac Interrupting Rating | 18 KAIC |
| 120/240 Vac Interrupting Rating | 18 KAIC |
| 125 Vdc Interrupting Rating | 10 KAIC |
| 240 Vac Interrupting Rating | 18 KAIC |
| 250 Vdc Interrupting Rating | 10 KAIC |
| 277 Vac Interrupting Rating | 18 KAIC |
| 480 Vac Interrupting Rating | 18 KAIC |
| 500 Vdc Interrupting Rating | 10 KAIC |
| 600 Vac Interrupting Rating | 14 KAIC |
| Trip Function | LI |
| Continuous Current Rated | Standard |
| Suitable for Reverse Feed | Yes |
| Lugs | TC041, TCAL14 |
| Long Time | Fixed |
| Instantaneous | Fixed |
| Current Metering | No |
| Protective Relays | No |
| Special Markings | HACR |
| UL File# | E11592 |
| CSA File# | LR57114 |
| GSA Compliance | Yes |
| GO Schedule | 135B |
| UPC | 078316406301 |
| List Price | \$377 |







Publications/Resources

TED134015WL

Additional Resources for Thermal Magnetic

Application and Technical Brochures Data Sheets Drawings-Outline and Dimensional Installation and Instruction **Time Current Curves** White Papers BIM Files Buy Log :3-30

The E150 product line consists of Thermal Magnetic

Circuit Breakers, Magnetic Circuit Breakers, and Molded-Case Switches rated up to 150 Amps and 600 Volts AC. Catalog numbers include the complete breaker or switch. The WL catalog number suffix indicates that the devices come with Cu/Al line and load lugs.

