

# DTU224NRB

Safety switch, double throw, non fusible, 200A, 240 VAC/250 VDC, 2 poles, 15 hp, neutral, NEMA 3R, bolt on



## Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	2
Voltage Rating	240 V AC
Wire Size	AWG 6...300 kcmil copper or aluminium

## Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	15 hp 240 V AC 50...60 Hz 1 phase NEC 240.6
Maximum Width	24 in (609.60 mm)
Maximum Height	32.5 in (825.50 mm)
Maximum Depth	10.63 in (270.00 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil

## Ordering and shipping details

Category	00133 - DT SWITCH,NEMA3R
Discount Schedule	DE1
GTIN	00785901174523
Nbr. of units in pkg.	1
Package weight(Lbs)	69.86 lb(US) (31.69 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 in (27.94 cm)
Package 1 width	23.20 in (58.928 cm)
Package 1 Length	34.20 in (86.868 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>

Contractual warranty

Warranty	18 months
----------	-----------