



## Main

|                             |   |
|-----------------------------|---|
| Product or Component Type   | Circuit breaker                                     |
| Range                       | PowerPact P   |
| Current Sensor Rating Range | 1200 A  |
| Rated Current               | 1200 A  |
| Breaking Capacity           | 100 KA 240 V AC<br>65 KA 480 V AC<br>25 kA 600 V AC |
| Trip Unit Technology        | Electronic, basic, ET 1.0I, LI                      |
| AWG Gauge                   | AWG 3/0...500 kcmil aluminium/copper)4              |

## Complementary

|                             |   |
|-----------------------------|---|
| Certifications              | IEC<br>UL Listed<br>CSA   |
| Rated operational Voltage   | 600 V AC  |
| Module Type                 | P-Frame   |
| Mounting Location           | Busbar  |
| Mounting Mode               | I-Line  |
| Poles Description           | 3P  |
| Circuit Breaker Rating Code | J   |
| Continuous Current Rating   | 80 %  |
| Electrical Connection       | I-Line connection line<br>Lugs load   |
| Tightening Torque           | 442.54 Lbf.in (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil<br>8.85...11.51 lbf.in (1.0...1.3 N.m) |
| Height                      | 16.16 in (410.46 mm)  |
| Width                       | 8.27 in (210.06 mm)   |
| Depth                       | 8.05 in (204.47 mm)   |

## Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 01210 - PG,H,J,K,L,N I-LINE BREAKERS |
| Discount Schedule     | DE2                                  |
| GTIN                  | 00785901282259                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 37.54 lb(US) (17.03 kg)              |
| Returnability         | Yes                                  |
| Country of origin     | US                                   |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 12.50 in (31.750 cm) |
| Package 1 width  | 12.10 in (30.734 cm) |
| Package 1 Length | 20.80 in (52.832 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | <a href="#">End Of Life Information</a>  |
| PVC free                   | Yes  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|