

HU361DF

Safety switch, heavy duty, non fusible, 30A,
3 poles, 30 hp, 600 VAC/DC, NEMA 4X,
fiberglass reinforced polyester



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4X fiberglass reinforced polyester
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	20 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 30 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 15 hp 600 V DC NEC 430.52
Maximum Height	16.5 in (419.10 mm)
Maximum Depth	8.8 in (223.52 mm)
Maximum Width	11 in (279.40 mm)
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in ² (13.3 mm ²) AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10)

Ordering and shipping details

Category	00111 - H&HU SW,N4X(DF,DX)NON-MET
Discount Schedule	DE1
GTIN	00785901627890
Nbr. of units in pkg.	1
Package weight(Lbs)	20.12 lb(US) (9.13 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	11.30 in (28.702 cm)
Package 1 width	12.50 in (31.750 cm)
Package 1 Length	19.80 in (50.292 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------